

ELAC

Klang lebt

[Line 260]

Ready – for a musical adventure



Let yourself be carried away by the effortless sound of the two latest additions to the ELAC portfolio, and set off on an unforgettable musical adventure.

www.elac.com



Line 260

Inner strengths – wrapped in a beautiful exterior

With their graceful curved cabinets, even the design of the loudspeakers in the Line 260 creates an impression of agility that is also reflected in their performance.

Equipped with the finest components available such as the JET 5, a crossover that makes exclusive use of air-core coils and foil capacitors, as well as Van den Hul cabling and magnetically fixed baffle covers, the Line 260 is the rightful successor to the celebrated Line 240 Black Edition.



- ◀ BS 263: Terminal
- ▼ FS 267: High Power Air Coil





A perfect pair



BS 263

Do not be deceived by the compact dimensions of the BS 263. Focus instead on its exceptionally grown-up sound! The fact that the cabinet is enlarged progressively towards the front baffle ensures that bass runs and counterpoint - even in the lowest registers - are effortlessly reproduced.

FS 267

As the slender sibling of the compact BS 263, the FS 267 with its convex curved cabinet typical of the 260 Line fits discreetly - almost organically - into every listening room. Close your eyes and embark on a journey...



- ◀ *BS 263
with and without
a fabric grille*
- ▶ *FS 267
Bottom plate with
Ultimate Spikes*



Technical specifications



| | FS 267 | BS 263 |
|-------------------------------------|---|--|
| Height x Width x Depth | 1,021 x 240 x 285 mm | 285 x 192 x 285 mm |
| Weight | 19.8 kg | 6.6 kg |
| Type | 2 ½-way, bass reflex | 2-way, bass reflex |
| Woofer | 2 x 150 mm, AS XR cone | 1 x 150 mm, AS XR cone |
| Tweeter | JET 5 | JET 5 |
| Magnetic shielding | – | – |
| Crossover frequency | 500 2,500 Hz | 2,500 Hz |
| Frequency range (IEC 268-5) | 30 to 50,000 Hz | 41 to 50,000 Hz |
| Sensitivity | 88.5 dB at 2.83 V/m | 87 dB at 2.83 V/m |
| Suitable for amplifiers from ... to | 4 - 8 Ω | 4 - 8 Ω |
| Recommended amplifier power | 30 - 250 W/channel | 30 - 150 W/channel |
| Nominal- Peak power handling | 120 W 160 W | 60 W 80 W |
| Nominal- Minimum impedance | 4 Ω 3.4 Ω at 190 Hz | 4 Ω 3.6 Ω at 230 Hz |
| Finishes | Black High Gloss | Black High Gloss |
| Accessories included in delivery | Fabric grille, magn. fixed; set of Ultimate Spikes | Fabric grille, magn. fixed |
| Optional accessories | | LS 30 speaker stand height: 700 mm, base: 270 x 330 mm (W x D), Black Lacquer High Gloss, Black Lacquer Satin Matte, White Lacquer High Gloss |

Errors and omissions excepted. Specifications and design features subject to change without notice.



ELAC Electroacoustic GmbH
Rendsburger Landstraße 215 • 24113 Kiel • Germany
Tel. +49-431-64774-0 • www.elac.com