

McIntosh®

DS200 STREAMING DAC



ROON READY

ROON TESTED



- The McIntosh DS200 Streaming DAC is the ultimate solution for music enthusiasts who demand the perfect blend of high-end audio quality and seamless streaming capabilities.
- This user-friendly streamer offers a variety of built-in casting technologies to play your streamed music.

- No special control app or technical skills are needed to use the DS200. You can easily stream your favorite music directly to the DS200 from your smart device.
- Compatible with Qobuz Connect, Spotify® Connect, and TIDAL® Connect, which let you stream your music seamlessly from the cloud straight to your devices.

- Additional streaming options included are Apple® AirPlay®, Bluetooth®, and Google Cast™.
- Utilizes Bluetooth 5.0, the high bitrate Advanced Audio Coding (AAC) standard, Qualcomm® aptX™ HD for hi res audio playback, and Qualcomm aptX Low Latency.
- Powered by a next generation, Quad Balanced, 8-channel, 32-bit audiophile-grade DAC

that features huge dynamic range and low distortion for pristine sound reproduction.

- Features 8 digital inputs and a pair of balanced and unbalanced analog outputs. Outputs can be used in either fixed or variable volume mode.
- Supports high resolution digital audio playback.

McIntosh®

DS200 STREAMING DAC



ELECTRONIC SPECIFICATIONS

Frequency Response

+/-0.5dB from 20Hz to 20kHz
+0.5/-3dB from 5Hz to 60kHz (source dependent)

Total Harmonic Distortion

0.005%

Fixed Output Level

2.0Vrms Unbalanced
4.0Vrms Balanced

Adjustable Output Level

0 - 8.0Vrms Unbalanced
0 - 16.0Vrms Balanced

Signal To Noise Ratio

100dB

Dynamic Range

100dB

Output Impedance

100 ohms Unbalanced and Balanced

CONNECTIVITY

Digital Coaxial Input: 2

Digital Optical Input: 2

Digital USB Input: 1

Digital MCT Input: 1

Digital AES/EBU Input: 1

HDMI Input: 1 (ARC)

Wireless Input

Wi-Fi: a, b, g, n, ac; 2.4/5 GHz

Bluetooth 5.0: AVRCP, A2DP, aptX, aptX HD, aptX LL

Streaming Support

AirPlay, Google Cast, Qobuz Connect, Roon, Spotify Connect, Tidal Connect

Balanced Output: 1 (can be set to either fixed or variable mode)

Unbalanced Output: 1 (can be set to either fixed or variable mode)

Network Connection: 1

DIGITAL AUDIO SPECIFICATIONS

Digital-to-Analog Converter (DAC) Type

8-channel, 32-bit/384kHz PCM/DSD, Quad Balanced

Digital Coaxial Input Sample Rate

24-bit/44.1kHz to 192kHz

Digital Optical Input Sample Rate

24-bit/44.1kHz to 192kHz

Digital MCT Input Sample Rate

16-bit/44.1kHz (CD)
DSD64 (SACD)

Digital USB Input Sample Rate

32-bit/44.1kHz to 384kHz (PCM)
DSD64, DSD128, DSD256, DSD512, DXD352.8kHz, DXD384kHz

Digital Network/Wi-Fi Input

Sample Rate
24-bit/44.1kHz to 192kHz

CONTROL

Power Control Input: 1

Power Control Output: 1

Rear Panel Data Input: 1

Rear Panel IR Sensor Input: 1

RS232 Control Input: 1

WEIGHTS & DIMENSIONS

Unit Dimensions (W x H x D)

17-1/2" (44.5cm) x 6" (15.2cm) x 17" (43.2cm)

Unit Weight

20.5 pounds (9.3 kg)

Shipping Weight

27.5 pounds (12.5 kg)

Learn more:

Visit mcintoshlabs.com



DISCOVER DS200